

SAFETY DATA SHEET

EcoSolv E

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name
EcoSolv E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
Cleaning product
Restricted to professional users.

Uses advised against
None known.

1.3. Details of the supplier of the safety data sheet

Company and address
Solveco AB
Tallbacksgatan 10
S-195 72 Rosersberg
Sweden
T: +46 (0)8 732 72 75
F: +46 (0)8 732 72 76
<http://www.solveco.se>

Contact person
Habib Hourani

E-mail
info@solveco.se

Revision
21/05/2024

SDS Version
3.0

Date of previous version
26/03/2024 (2.0)

1.4. Emergency telephone number

In urgent situations: Call 112 and request the poison information centre. (24h service)
In less severe situations: Call 010-456 6700 (24h service)
See also section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.
Flam. Liq. 3; H226, Flammable liquid and vapour.
Eye Irrit. 2; H319, Causes serious eye irritation.
STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s)



Signal word
Danger

Hazard statement(s)

Highly flammable liquid and vapour. (H225)
 Flammable liquid and vapour. (H226)
 Causes serious eye irritation. (H319)
 May cause drowsiness or dizziness. (H336)

Precautionary statement(s)

General

-

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
 Wear face protection/protective gloves/protective clothing. (P280)

▼ Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
 If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal

Dispose of contents/container in accordance with local regulation (P501)

▼ Hazardous substances

ethanol;ethyl alcohol
 1-methoxy-2-propanol;monopropylene glycol methyl ether
 Isopropanol
 Methyl ethyl ketone
 2-methylpropan-2-ol;tert-butyl alcohol

Additional labelling

Not applicable.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
 This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
ethanol;ethyl alcohol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH: 01-2119457610-43-XXXX Index No.: 603-002-00-5	60-80%	Flam. Liq. 2, H225 Eye Irrit. 2, H319	
1-methoxy-2-propanol;monopropylene glycol methyl ether	CAS No.: 107-98-2 EC No.: 203-539-1 REACH: Index No.: 603-064-00-3	15-25%	Flam. Liq. 3, H226 STOT SE 3, H336	[1]
Isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: Index No.: 603-117-00-0	5-10%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
Methyl ethyl ketone	CAS No.: 78-93-3 EC No.: 201-159-0 REACH: Index No.: 606-002-00-3	<1%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
2-methylpropan-2-ol;tert-butyl	CAS No.: 75-65-0	<1%	Flam. Liq. 2, H225	

alcohol	EC No.: 200-889-7 REACH: 01-2119444321-51-XXXX Index No.: 603-005-00-1	Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335
---------	--	---

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are

produced. These are:
Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼ Control parameters

ethanol;ethyl alcohol

Short term exposure limit (15 minutes) (ppm): 1000

Short term exposure limit (15 minutes) (mg/m³): 1900

Long term exposure limit (8 hours) (ppm): 500

Long term exposure limit (8 hours) (mg/m³): 1000

Annotations:

V = Indicative short term limit.

1-methoxy-2-propanol;monopropylene glycol methyl ether

Short term exposure limit (15 minutes) (ppm): 150

Short term exposure limit (15 minutes) (mg/m³): 568

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 190

Annotations:

H = The substance is easily absorbed through the skin.

Isopropanol

Short term exposure limit (15 minutes) (ppm): 250

Short term exposure limit (15 minutes) (mg/m³): 600

Long term exposure limit (8 hours) (ppm): 150

Long term exposure limit (8 hours) (mg/m³): 350

Annotations:

V = Indicative short term limit.

Methyl ethyl ketone

Short term exposure limit (15 minutes) (ppm): 300

Short term exposure limit (15 minutes) (mg/m³): 900

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 150

Occupational exposure limits (AFS 2018:1) and later amendment AFS 2020:6 and AFS 2021:3.

▼ DNEL

1-methoxy-2-propanol;monopropylene glycol methyl ether

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	183 mg/kg kroppsvikt/dag
Long term – Local effects - Workers	Inhalation	553,5 mg/m ³
Long term – Systemic effects - Workers	Inhalation	369 mg/m ³

Isopropanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	888 mg/kg kroppsvikt
Long term – Systemic effects	Inhalation	500 mg/m ³

PNEC

Isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140,9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release		140,9 mg/L
Marine water		140,9 mg/L
Marine water sediment		552 mg/kg
Sewage treatment plant		2251 mg/L
Soil		28 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Work situation	Type	Class	Colour	Standards
If ventilation at the work place is insufficient, use a half- or full mask with an appropriate filter or an air-supplied breathing apparatus.	A	-	Brown	EN14387



Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn.	-	-



Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	-	-	EN374-2
Butyl	-	-	EN374-2, EN374-3, EN388, EN421



Eye protection

Type	Standards
In the likelihood of direct or incidental exposure, use face protection or safety glasses with side shields.	EN166

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Colourless

Odour / Odour threshold

Alcohol odor

pH

Testing not relevant or not possible due to the nature of the product.

Density (g/cm³)

0,75-0,8

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes**Melting point/Freezing point (°C)**

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards**Flash point (°C)**

10-15

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

2 - 19

Solubility**Solubility in water**

Completely soluble

n-octanol/water coefficient (LogKow)

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information**Other physical and chemical parameters**

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance ethanol;ethyl alcohol
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50 (4 hours)
 Result: 124,7 mg/L

Product/substance ethanol;ethyl alcohol
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: 7060 mg/kgbw

Product/substance ethanol;ethyl alcohol
 Species: Rabbit
 Route of exposure: Dermal
 Test: LD50
 Result: >20000 mg/kgbw

Product/substance ethanol;ethyl alcohol
 Species: Human
 Route of exposure: Oral
 Test: LD lo
 Result: 2 mg/kgbw

Product/substance 1-methoxy-2-propanol;monopropylene glycol methyl ether
 Species: Fish
 Route of exposure: Oral
 Test: LC50
 Result: 6812 (96h) mg/L

Product/substance 1-methoxy-2-propanol;monopropylene glycol methyl ether
 Species: Daphnia magna
 Route of exposure: Oral
 Test: LC50
 Result: 23300 (48h) mg/L

Product/substance 1-methoxy-2-propanol;monopropylene glycol methyl ether
 Species: Algae
 Test: EC50
 Result: >1000 (96h) mg/L

Product/substance 1-methoxy-2-propanol;monopropylene glycol methyl ether
 Species: Mouse
 Route of exposure: Oral
 Test: LD50
 Result: 11700 mg/kg

Product/substance 1-methoxy-2-propanol;monopropylene glycol methyl ether
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50
 Result: 10000 (5h) ppm

Product/substance 1-methoxy-2-propanol;monopropylene glycol methyl ether
 Species: Rabbit
 Route of exposure: Dermal
 Test: LD50
 Result: 13000 mg/kg

Product/substance	Isopropanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	4396.00 mg/kg

Product/substance	Isopropanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	12800.00 mg/kg

Product/substance	Isopropanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	46.5-72.0 mg/L

Skin corrosion/irritation

Product/substance	1-methoxy-2-propanol;monopropylene glycol methyl ether
Test method:	OECD 404
Species:	Rabbit
Duration:	4 hours
Result:	No adverse effect observed (Not irritating)

▼ Serious eye damage/irritation

Product/substance	ethanol;ethyl alcohol
Test method:	(mod. Draize)
Species:	Rabbit
Duration:	72 hours
Result:	Adverse effect observed (Highly irritating)

Product/substance	1-methoxy-2-propanol;monopropylene glycol methyl ether
Test method:	OECD:s riktlinjer för test 405
Species:	Rabbit
Duration:	Single exposure

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance	1-methoxy-2-propanol;monopropylene glycol methyl ether
Test method:	OECD 406
Species:	Guinea pig
Result:	No adverse effect observed (not sensitising)

Germ cell mutagenicity

Product/substance	1-methoxy-2-propanol;monopropylene glycol methyl ether
Test method:	OECD guideline 471
Species:	salmonella typhimurium
Conclusion:	No adverse effect observed

Carcinogenicity

Product/substance	1-methoxy-2-propanol;monopropylene glycol methyl ether
Test method:	OECD guideline 453
Species:	Rat
Test:	OECD guideline 453
Result:	not carcinogenic
Conclusion:	No adverse effect observed

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

Isopropanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance	ethanol;ethyl alcohol
Species:	Fish, Pimephales promelas
Compartment:	Water
Duration:	96 hours
Test:	LC50
Result:	13500 mg/L

Product/substance	Isopropanol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	4200.00 mg/L

Product/substance	Isopropanol
Species:	Algae (Scenedesmus subspicatus)
Duration:	96 hours
Test:	IC50
Result:	>1000.00 mg/L

Product/substance	Isopropanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	13299.00 mg/L

12.2. ▼ Persistence and degradability

Product/substance	ethanol;ethyl alcohol
Result:	85 % bryts ner på 28 Dygn
Conclusion:	Readily biodegradable
Test:	OECD 301 D

Product/substance	Isopropanol
Result:	84 %
Conclusion:	Readily biodegradable
Test:	OECD 301 C

12.3. ▼ Bioaccumulative potential

Product/substance	ethanol;ethyl alcohol
BCF:	0,66
LogKow:	-0,32
Conclusion:	No potential for bioaccumulation

Product/substance	1-methoxy-2-propanol;monopropylene glycol methyl ether
-------------------	--

Conclusion: No potential for bioaccumulation

Product/substance: Isopropanol
Conclusion: No potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

Dispose of contents/container to an approved waste disposal plant.

SFS Waste regulation (2020:614).

EWC code

20 01 13* Solvents

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	1987	ALCOHOLS, N.O.S. (ETHANOL, ISOPROPANOL)	Transport hazard class: 3 Label: 3 Classification code: F1	II	No	Tunnel restriction code: 2 (D/E) See below for additional information.
IMDG	1987	ALCOHOLS, N.O.S. (ETHANOL, ISOPROPANOL)	Transport hazard class: 3 Label: 3 Classification code: F1	II	No	EmS: F-E S-D See below for additional information.
IATA	UN1987	ALCOHOLS, N.O.S.	Transport hazard class: 3 Label: 3 Classification code: F1	II	No	See below for additional information.



* Packing group

** Environmental hazards

▼ Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or

accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not work with this product. This does not apply if the working task is:

- performed by young people who have completed upper secondary education or equivalent education for the task or
- included in teaching that is located in a school premises or other place that is specially arranged for teaching, or
- included in supervisor-led internships for young people, or
- of such a nature that the risk of injury is considered to be minimal.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

▼ Regulation on drug precursors

Methyl ethyl ketone is included (Category 3)

REACH, Annex XVII

ethanol;ethyl alcohol is subject to REACH restrictions, REACH annex XVII (entry 40).

1-methoxy-2-propanol;monopropylene glycol methyl ether is subject to REACH restrictions, REACH annex XVII (entry 40).

Isopropanol is subject to REACH restrictions, REACH annex XVII (entry 40).

Methyl ethyl ketone is subject to REACH restrictions, REACH annex XVII (entry 40).

Additional information

Not applicable.

▼ Sources

The Swedish Work Environment Authority's provisions on young peoples' work environment (AFS 2012:3).

The Swedish Work Environment Authority's regulations and general guidelines (AFS 2007:5) on pregnant and breastfeeding workers with later amendments, latest AFS 2018:7.

The Swedish Civil Contingencies Agency 2015:8 regulations on measures to prevent and limit the consequences of serious chemical accidents.

SFS Waste regulation (2020:614).

Council Regulation (EC) No 273/2004 on drug precursors.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H314, Repeated exposure may cause skin dryness or cracking.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the mixture in regard to physical hazards has been based on experimental data.

▼ The safety data sheet is validated by

Christian Andersson

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: SE-en